



High Performance Information Outlets



Height	4.85" / 12.32 cm
Width	3.0" / 7.62 cm
Depth	1.0" / 2.54 cm

Factory assembled or ...

... components



Description	Part Number
Single w/ 110 Connectors	HO-FB-01
Dual w/ 110 Connectors	HO-FB-02
Triple w/ 110 Connectors	HO-FB-03
Quad w/ 110 Connectors	HO-FB-04
Components	
Faceplate with Hardware	HO-FB-FP
Dustcover for Faceplate	HO-DC
Icons (12 per pkg)	HO-ICONS
Single 110 Connector	SINGLE
Dual 110 Connector	DUAL

- Exceeds Category 5e performance on all pairs
- EIA/TIA 568A or 568B standard
- Port identification icons / ample labeling area
- Port identification icons available in 9 colors
- Accepts 3/8" or 9 mm label from Brother P-Touch printer
- Shallow wall cavity mounting of only 1 inch
- ABS plastic meets requirement for UL-rated 94V-O
- Choice of 110, Katt, or Krone IDC blocks
- Printed circuit board technology for impedance-matched performance
- Single, dual, triple, or quad – add ports in the future without making existing outlet obsolete
- Adequate port spacing allows for proper wire management and bend radius compliance
- Factory assembled or available as components